WWW.IRUDEK.COM



SHOCKER
Y 180HSHS

IRUDEK

IRUDEK 2000 SL - POL. ERRIBERA, S.A
20150 ADUNA (GIPUZKOA) SPAIN

ABSORBEDOR DE ENERGÍA

FICHA TÉCNICA

Descripción

- Absorbedor de energía con doble cinta.
- Diseñado para soportar caídas y reducir el impacto de caída.
- Chip NFC Ready: Chip incorporado para trazabilidad de producto, estado y revisión.

CARACTERÍSTICAS

Características generales	Longitud	1,80m
	Peso	2500g
	Vida útil	10 años de uso + 2 años de almacenamiento
Características técnicas	Capacidad de uso	140kg
	Norma	ANSI Z359.13
	Resistencia cierre	16kN (3600lbs)
	Ancho cinta	30mm
	Distancia máxima de despliegue	1,20m

	Componente	Material
Materiales	Absorbedor	Poliéster
	Cinta	Poliéster
	Ganchos	Acero

	Componente	Material	Abertura
Conectores	Gancho pequeño	Acero	21mm
	Gancho grande	Acero	66mm

ENERGY ABSORBER

Description

- Energy absorber with double tape.
- Designed to withstand falls and reduce fall impact.
- NFC Ready Chip: Built-in chip for product traceability, status and revision.

CHARACTERISTICS

General characteristics	Length	1,80m
	Weight	2500g
	Shelf life	10 years of use + 2 years of storage
Technical characteristics	Capacity to use	140kg
	Norma	ANSI Z359.13
	Closing resistance	16kN (3600lbs)
	Tape width	30mm
	Maximum deployment distance	1,20m

	Component	Material
Materials	Absorber	Polyester
	Tape	Polyester
	Hooks	Steel

	Component	Material	Opening
Connectors	Small hook	Steel	21mm
	Large hook	Steel	66mm