



CXL 130-1LW-SS-Ex

ATEX certified, 0 dBd, Omnidirectional Base Station Antenna for the International 118 - 137 MHz Band in Hazardous areas



DESCRIPTION

- CXL 130-1LW-SS-Ex is a 0 dBd, vertically polarized, omnidirectional base station antenna which covers the 118 – 137 MHz band in Hazardous areas.
- The antenna is specified as an ATEX antenna for use in zone 2 in potentially explosive areas.
- Before installing the antenna, please read the ATEX Product Manual carefully.
- The antenna is suitable for use in gas groups IIA, IIB and IIC in zone 2.
- It's only necessary to install an ATEX grounding Kit on the LW-SS-Ex bracket, when the point of installation has a different electrical potential than the system.
- The antenna is a broad-banded $\frac{1}{2} \lambda$ dipole design.
- The accompanying U-bolts and fittings are made of stainless steel.
- The antenna element is sealed in high-quality glass fibre tube.
- All metal parts in the antenna are DC-grounded. Consequently, the antenna shows a DC-short across the coaxial cable.

SPECIFICATION

Last Update: 07/10/2026 07:09 AM

ELECTRICAL

Model	CXL 130-1LW-SS-Ex
Frequency	118 – 137 MHz
Antenna Type	Coaxial dipole, broad-banded
Special spec. info	Max. RF Input Power due to max. EIRP in ATEX Environment *: Group IIA : 35.6 dBm (3.6 W) Group IIB : 33.3 dBm (2.1 W) Group IIC : 30.8 dBm (1.2 W)
Polarisation	Vertical
Pattern Type	Omnidirectional
3 dB Beamwidth, E-Plane	80 °
3 dB Beamwidth, H-Plane	Omnidirectional
Impedance	50 Ω
Gain	0 dBd (2.2 dBi)
VSWR	< 1.75:1
Bandwidth	19 MHz
Antistatic Protection	All metal parts DC-grounded (Connector shows a DC-short)
HCM Code(s)	HCM000ND00, 040DE00

ENVIRONMENTAL

Operating temperature range	-30 °C to +60 °C
Survival Wind Speed	200 km/h
Ingress Protection	IP66

MECHANICAL

Connector Torque	N(f) : 0.7 – 1.1 Nm
Materials	Radome : Polyurethane-coated glass fibre Mounting bracket : Stainless acid-proof steel (AISI 316L) U-bolt and fittings : Stainless steel (AISI 316)
Installation Torque	3 Nm
Colour	Blue (RAL 5015)
Historic Brand	Amphenol Procom
Special Feature / Application	ATEX
Wind Area	0.023 sq. m / 0.25 sq. ft
Wind Load	29 N (160 km/h)
Dia. At Top End	17 mm / 0.67 in.
Dia. At Bottom End	23 mm / 0.91 in.
Height	Approx. 1500 mm / 59.06 in.
Weight	Approx. 1.25 kg / 2.76 lb.
Mounting	On 16 to 54 mm / 0.63 – 2.13 in. dia. mast tube
ATEX Marking	II 3G Ex nA IIC T6

ORDERING CODES

MODEL	PRODUCT NO.
ATEX certified, 0 dBd, Omnidirectional Base Station Antenna for the International 118 – 137 MHz Band in Hazardous areas	115000001


ADDITIONAL INFORMATION

Calculation of max. Antenna input power in different ATEX groups


ATEX GROUP	MAX. EIRP POWER	ANTENNA GAIN	MAX INPUT POWER
IIA	37.7 dBm (6.0 W)	0 dBd / 2.15 dBi	35.6 dBm (3.6 W)
IIB	35.4 dBm (3.5 W)	0 dBd / 2.15 dBi	33.3 dBm (2.1 W)
IIC	33.0 dBm (2.0 W)	0 dBd / 2.15 dBi	30.8 dBm (1.2 W)

*See the ATEX Product Manual (safety and mounting instructions) and related EU DECLARATION OF CONFORMITY ATEX Directive 2014/34/EU.


Typical Gain and VSWR curve



Typical Radiation Pattern (E-Plane)



Typical Radiation Pattern (H-Plane)



Mounting Details

